



## 13" HISTORIC SLICKS

For use on Classic and Historic racing applications.



TYRE SIZE	RIM CHOICE	RIM USED	MEASURED AT		DIAMETER		SECTION		TREAD		REVOLUTIONS		COMPOUND AVAILABLE	CATEGORY
			PSI	BAR	INS	MM	INS	MM	INS	MM	INS	MM		
9.0/20.0-13	8.0 - 10.0	10	20	1.36	20.00	508	10.65	271	9.20	233	1008	630	A11	HF2 / GP6
10.0/20.0-13	9.0 - 11.0	10	20	1.36	19.80	502	11.10	282	10.20	259	1018	636	A11	HF1
6.5/21.0-13	5.5 - 7.5	7	20	1.36	20.50	520	9.00	229	6.50	165	984	615	A46	FF2000
7.0/21.0-13	6.0 - 8.0	8	20	1.36	20.60	523	9.00	229	7.20	182	979	612	A11	HSC
8.2/22.0-13	7.0 - 10.0	9	20	1.36	22.00	558	10.10	257	8.60	218	917	573	A11, A46	FF2000 / GP6
9.2/22.0-13	8.5 - 10.5	10	20	1.36	22.40	568	11.10	282	9.10	231	900	562	A37	HF3
9.2/22.0-13	8.5 - 10.5	10	20	1.36	22.40	568	11.10	282	9.10	231	900	562	A11	HSC
10.0/22.0-13	9.0 - 12.0	11	20	1.36	22.10	561	11.90	302	10.30	261	912	570	A11	HSC
10.5/23.0-13	9.5 - 11.5	11	20	1.36	23.50	596	12.30	312	10.30	261	858	536	A11	HF1
10.5/23.0-13	9.5 - 11.5	11	20	1.36	23.50	596	12.30	312	10.30	261	858	536	A11	HSC
12.0/23.0-13	12.0 - 14.0	13	20	1.36	23.20	589	14.50	368	12.30	312	869	543	A11	HF2 / GP6
13.0/23.0-13	13.0 - 15.0	14	20	1.36	23.25	590	15.15	385	13.00	330	867	542	A11	HF2 / GP6
14.0/23.0-13	14.0 - 15.0	14	20	1.36	23.25	590	15.55	395	13.60	345	867	542	A24	GPC
13.0/24.5-13	13.0 - 15.0	14	20	1.36	24.30	617	15.50	394	12.50	317	830	519	A11	GP6
15.0/26.0-13	15.0 - 18.0	16	20	1.36	25.75	654	17.75	451	15.00	381	783	489	A11	HF1
16.2/26.0-13	16.0 - 18.0	17	20	1.36	25.80	655	18.75	476	16.30	414	782	489	A11	HF1
16.2/26.0-13	16.0 - 18.0	17	20	1.36	25.80	655	18.75	476	16.30	414	782	489	A11	HSC