

16" HISTORIC SLICKS

For use on Classic and Historic racing applications.



TYRE SIZE	RIM CHOICE	RIM USED	MEASURED AT		DIAMETER		SECTION		TREAD		REVOLUTIONS		COMPOUND AVAILABLE	CATEGORY
			PSI	BAR	INS	MM	INS	MM	INS	MM	MILES	KM		
10.0/23.5-16	9.0 - 11.0	10	30	2.04	23.60	599	10.95	278	10.00	254	854	534	A11,A24	GPC
11.0/23.5-16	10.0 - 12.0	12	30	2.04	23.50	596	12.55	319	11.30	287	858	536	A11,A24	GPC
11.0/23.5-16	10.0 - 12.0	12	30	2.04	23.50	596	12.55	319	11.30	287	858	536	A11, A24	GP2 / GP5
12.5/23.5-16	11.5 - 13.5	13.5	30	2.04	23.40	594	13.75	349	12.70	322	862	539	A11,A24	GPC
12.5/23.5-16	11.5 - 13.5	13.5	30	2.04	23.40	594	13.75	349	12.70	322	862	539	A11, A24	GP2 / GP5
12.5/25.0-16	11.5 - 13.5	13	30	2.04	24.75	628	14.20	361	12.50	317	815	509	A11, A24	GP2 / GP5
13.5/25.0-16	12.0 - 14.5	14	30	2.04	25.00	635	15.20	386	13.40	340	807	504	A11,A24	GPC
14.0/27.0-16	13.0 - 16.0	14	30	2.04	27.20	690	15.75	400	14.00	355	741	463	A11, A37	GPC
14.0/27.0-16	13.0 - 16.0	14	30	2.04	27.20	690	15.75	400	14.00	355	741	463	A37	HSC