



15" HISTORIC ALL WEATHER

The Avon Historic All Weather patterned tyres are designed to give exceptional road holding characteristic in all-weather applications while keeping the period look of the historic range of racing cars. It is FIA homologated for several historic racing series throughout the world.

TYRE SIZE	RIM CHOICE	RIM USED	MEASURED AT		DIAMETER		SECTION		TREAD		REVOLUTIONS		COMPOUND AVAIABLE	CATEGORY	PATTERN CODE
			PSI	BAR	INS	MM	INS	MM	INS	MM	MILES	KM			
8.7/21.5-15	7.5 - 9.0	8	30	2.04	22.10	561	9.70	246	8.40	213	912	570	A53	GN	H003
9.5/21.5-15	8.0 - 10.0	10	30	2.04	21.85	554	10.65	271	9.50	241	923	577	A15	GC	H004
10.0/21.5-15	8.5 - 11.0	10	30	2.04	21.85	554	11.00	279	10.00	254	923	577	A24	GC	H005
10.0/21.5-15	8.5 - 11.0	10	30	2.04	21.85	554	11.00	279	10.00	254	923	577	A53	GH	H005
10.7/21.5-15	9.0 - 11.0	10	30	2.04	21.85	554	11.30	287	10.60	269	923	577	A11, A24	GC	H005
7.5/23.0-15	7.0 - 8.5	8	30	2.04	22.80	579	8.50	216	7.40	187	884	552	A24	HSC	H002
10.5/23.0-15	10.0 - 12.0	11	30	2.04	23.55	598	11.95	304	10.30	261	856	535	A11, HSC	HSC	H005
10.5/23.0-15	10.0 - 12.0	11	30	2.04	23.55	598	11.95	304	10.30	261	856	535	A37	CER	H005
8.5/23.5-15	7.0 - 9.5	8.5	30	2.04	23.60	599	9.60	244	8.80	223	854	534	A49, A24	HSC	H003
8.5/23.5-15	7.0 - 9.5	8.5	30	2.04	23.60	599	9.60	244	8.80	223	854	534	A15	HC	H003
8.5/23.5-15	7.0 - 9.5	8.5	30	2.04	23.60	599	9.60	244	8.80	223	854	534	A60	GA	H003
8.5/23.5-15	7.0 - 9.5	8.5	30	2.04	23.60	599	9.60	244	8.80	223	854	534	A37	CER	H003
9.1/23.5-15	8.0 - 9.5	8.5	30	2.04	23.55	598	9.88	251	8.50	215	856	535	A11, A24	HSC	H004
9.1/23.5-15	8.0 - 9.5	8.5	30	2.04	23.55	598	9.88	251	8.50	215	856	535	A15	CLUB	H004
9.1/23.5-15	8.0 - 9.5	8.5	30	2.04	23.55	598	9.88	251	8.50	215	856	535	A29	GB	H004
9.1/23.5-15	8.0 - 9.5	8.5	30	2.04	23.55	598	9.88	251	8.50	215	856	535	A37	CER	H004
11.0/23.5-15	10.0 - 12.0	11	30	2.04	23.30	591	12.10	307	11.30	287	865	541	A11, A24	HSC	H006
11.0/23.5-15	10.0 - 12.0	11	30	2.04	23.30	591	12.10	307	11.30	287	865	541	A37	CER	H006
12.5/23.5-15	11.0 - 13.5	12	30	2.04	23.30	591	13.30	338	12.70	322	865	541	A15	GC	H007
9.0/25.0-15	9.0 - 11.0	10	30	2.1	24.75	629	10.10	257	8.90	226	815	506	A24	HSC	H004
11.0/25.0-15	10.0 - 12.0	12	30	2.04	24.70	627	13.60	345	11.30	287	816	510	A24	HSC	H006
13.0/25.0-15	11.5 - 14.0	14	30	2.04	24.80	629	15.40	391	13.20	335	813	508	A11, A24	HSC	H007
13.0/25.0-15	11.5 - 14.0	14	30	2.04	24.80	629	15.40	391	13.20	335	813	508	A37	CER	H007
15.0/26.0-15	15.0 - 17.0	16	30	2.04	25.75	654	17.40	442	15.00	381	783	489	A11, A24	HSC	H009
15.0/26.0-15	15.0 - 17.0	16	30	2.04	25.75	654	17.40	442	15.00	381	783	489	A37	CER	H008
16.2/26.0-15	16.0 - 18.0	16	30	2.04	25.80	655	17.90	455	16.30	414	782	489	A11	HSC	H009
12.5/27.0-15	11.5 - 14.5	13	30	2.04	27.00	685	15.25	387	12.50	317	747	467	A24	HSC	H007
14.0/27.0-15	13.0 - 16.0	15	30	2.04	27.10	688	16.70	424	14.00	355	744	465	A11, A24	HSC	H008
16.0/27.0-15	15.0 - 18.0	16	30	2.04	27.50	698	16.80	427	16.10	408	733	458	A11	HSC	H009