



15" HISTORIC SLICKS

For use on Classic and Historic racing applications.



TYRE SIZE	RIM CHOICE	RIM USED	MEASURED AT		DIAMETER		SECTION		TREAD		REVOLUTIONS		COMPOUND AVAILABLE	CATEGORY
			PSI	BAR	INS	MM	INS	MM	INS	MM	INS	MM		
10.5/23.0-15	10.0 - 12.0	11	30	2.04	23.55	598	11.95	304	10.30	261	856	535	A11	HF1
8.5/23.5-15	7.0 - 9.5	8.5	30	2.04	23.60	599	9.60	244	8.80	223	854	534	A24	SPTS
9.1/23.5-15	8.0 - 9.5	8.5	30	2.04	23.55	598	9.88	251	8.50	215	856	535	A11,A24	SPTS
11.0/23.5-15	10.0 - 12.0	11	30	2.04	23.30	591	12.10	307	11.30	287	865	541	A11, A24, A29	HSC
9.5/25.0-15	9.0 - 11.0	10	30	2.04	24.75	628	11.70	297	9.25	234	815	509	A24	HSC
11.0/25.0-15	10.0 - 12.0	12	30	2.04	24.70	627	13.60	345	11.30	287	816	510	A24	HSC
13.0/25.0-15	11.5 - 14.0	14	30	2.04	24.80	629	15.40	391	13.20	335	813	508	A11, A24	SPTS
13.0/25.0-15	11.5 - 14.0	14	30	2.04	24.80	629	15.40	391	13.20	335	813	508	A24, 310	HSC
15.0/26.0-15	15.0 - 17.0	16	30	2.04	25.75	654	17.40	442	15.00	381	783	489	A11	HF1
15.0/26.0-15	15.0 - 17.0	16	30	2.04	25.75	654	17.40	442	15.00	381	783	489	A24	HSC
16.2/26.0-15	16.0 - 18.0	16	30	2.04	25.80	655	17.90	455	16.30	414	782	489	A11	HF1
12.5/27.0-15	11.5 - 14.5	13	30	2.04	27.00	685	15.25	387	12.50	317	747	467	A24	HSC
14.0/27.0-15	13.0 - 16.0	15	30	2.04	27.10	688	16.70	424	14.00	355	744	465	A11	HSC
16.0/27.0-15	15.0 - 18.0	16	30	2.04	27.50	698	16.80	427	16.10	408	733	458	A11	HSC