



13" CLASSIC WET WEATHER

The Avon Classic Wet Weather patterned tyres are designed to give exceptional road holding characteristic when used in wet racing applications while keeping the period look with the classic range of racing cars throughout the world. It is a FIA homologated pattern.



TYRE SIZE	RIM CHOICE	RIM USED	MEASURED AT		DIAMETER		SECTION		TREAD		REVOLUTIONS		COMPOUND AVAILABLE	CATEGORY
			PSI	BAR	INS	MM	INS	MM	INS	MM	MILES	KM		
6.0/19.5-13	5.5 - 6.5	6	20	1.36	19.35	491	6.60	168	6.10	154	1042	651	A27	GA
8.0/19.5-13	7.0 - 9.0	8	20	1.36	19.30	490	8.70	221	7.90	200	1045	653	A15	GH
8.5/19.5-13	8.0 - 10.0	8	20	1.36	19.60	497	8.90	226	8.00	203	1029	643	A15	GH
7.5/20.0-13	6.5 - 8.5	8	20	1.36	20.25	514	9.00	229	7.70	195	996	622	A15	GA
8.2/20.0-13	7.0 - 9.0	9	20	1.36	19.95	506	9.75	248	8.50	215	1011	632	A15	GA
9.0/20.0-13	8.0 - 10.0	10	20	1.36	20.00	508	10.65	271	9.20	233	1008	630	A15	HSC
10.0/20.0-13	9.0 - 11.0	10	20	1.36	19.80	502	11.10	282	10.20	259	1018	636	A15	HSC
6.5/21.0-13	5.5 - 7.5	7	20	1.36	20.50	520	9.00	229	6.50	165	984	615	A27	FF2000
7.0/21.0-13	6.0 - 8.0	8	20	1.36	20.60	523	9.00	229	7.20	182	979	612	A27	HF3
7.5/21.0-13	6.5 - 8.5	8	20	1.36	20.50	520	8.50	216	7.40	187	984	615	A27, A37	HF3
9.2/22.0-13	8.5 - 10.5	10	20	1.36	22.40	568	11.10	282	9.10	231	900	562	A27, A37	HF3
10.0/22.0-13	9.0 - 12.0	11	20	1.36	22.10	561	11.90	302	10.30	261	912	570	A15	HSC
10.5/23.0-13	9.5 - 11.5	11	20	1.36	23.50	596	12.30	312	10.30	261	858	536	A15	HF1
12.0/23.0-13	12.0 - 14.0	13	20	1.36	23.20	589	14.50	368	12.30	312	869	543	A15	F2 / GP6
13.0/23.0-13	13.0 - 15.0	14	20	1.36	23.25	590	15.15	385	13.00	330	867	542	A15	F2 / GP6
13.0/24.5-13	13.0 - 15.0	14	20	1.36	24.30	617	15.50	394	12.50	317	830	519	A15	GP6
15.0/26.0-13	15.0 - 18.0	16	20	1.36	25.75	654	17.75	451	15.00	381	783	489	A15	HSC
16.2/26.0-13	16.0 - 18.0	17	20	1.36	25.80	655	18.75	476	16.30	414	782	489	A15	HF1